

	CTA	CTA Ref :
	Zurich actuator specifications C-series	EDMS id : Edition : 1.1 Date: 16.10.2012 Page : 1/1

Zurich actuator specifications, C-series

		Note:
Dimensions	260 – 296 mm x 65 mm (L x Ø)	Without gimbal
Weight	1570 g	Actuator
	370 g	Fixpoint
	600 g	1 dof gimbal
	920 g	2 dof gimbal
Power supply	18 – 24 VDC	
	≤ 850 mA	Driving current
	≤ 50 mA	Standby current
Communication	Wireless, industry standard (IEEE 802.15.4)	
Positioning	Absolute with angular sensor and Hall sensor	
Positioning precision	<5 µm with angular sensor only	
Mechanical clearance	± 10 µm	Without gimbals
Elevation speed	0.5 mm/s	
Full stroke length	36 mm	
Moving force	> 700 N	
Non destructive limit	> 9'600 N	
Degree of protection	IP 67	
Connectors	1 connector for power supply	
Holding force	Self-locking	
Built-in memory	4096 bytes = 2048 elevation angles	Look-up table
Lightning protection	integrated suppressor diode	

Contacts:

Stefan Steiner:	steiner@physik.uzh.ch
Achim Vollhardt	avollhar@physik.uzh.ch
Arno Gadola:	agadola@physik.uzh.ch